



HiTHERM N.A. LLC
 15000 Camino Real
 Kyle, Texas 78640
 (205) 961-0009
 HiTHERM.com

HiTHERM PIR300 25/50
 INSULATION THICKNESS TABLE (inches) TO LIMIT
 HEAT LOSS TO A MAXIMUM OF 8 BTU/HOUR-FT₂ **OUTDOORS**

Ambient temperature = 80°F Outer surface = Aluminum Jacketing Emissivity = 0.1
 Wind Velocity = 8 mph Geometry = Horizontal pipe

Nom Pipe Size (in)	SERVICE TEMPERATURE °F														
	-300	-250	-200	-150	-100	-80	-60	-50	-40	-30	-20	-10	0	+10	+20
0.5	2.5	2.5	2.5	2.5	2	2	1.5	1.5	1.5	1.5	1.5	1.5	1	1	1
0.75	3	2.5	2.5	2.5	2	2	2	2	1.5	1.5	1.5	1.5	1.5	1	1
1	3	3	3	2.5	2	2	2	2	1.5	1.5	1.5	1.5	1.5	1	1
1.25	3.5	3.5	3	3	2.5	2	2	2	1.5	1.5	1.5	1.5	1.5	1	1
1.5	3.5	3.5	3	3	2.5	2	2	2	2	1.5	1.5	1.5	1.5	1	1
2	3.5	3.5	3	3	2.5	2	2	2	2	1.5	1.5	1.5	1.5	1	1
2.5	3.5	3.5	3	3	2.5	2	2	2	2	1.5	1.5	1.5	1.5	1.5	1
3	4	3.5	3.5	3	2.5	2.5	2	2	2	2	1.5	1.5	1.5	1.5	1
4	4	4	3.5	3	3	2.5	2.5	2	2	2	2	1.5	1.5	1.5	1
5	4	4	4	3.5	3	2.5	2.5	2.5	2	2	2	1.5	1.5	1.5	1.5
6	4.5	4	4	3.5	3	2.5	2.5	2.5	2	2	2	2	1.5	1.5	1.5
8	4.5	4.5	4	3.5	3	2.5	2.5	2.5	2.5	2	2	2	1.5	1.5	1.5
10	5	4.5	4.5	4	3	3	2.5	2.5	2.5	2	2	2	1.5	1.5	1.5
12	5	5	4.5	4	3	3	2.5	2.5	2.5	2	2	2	1.5	1.5	1.5
14	5	5	4.5	4	3.5	3	3	2.5	2.5	2.5	2	2	1.5	1.5	1.5
16	5	5	4.5	4	3.5	3	3	2.5	2.5	2.5	2	2	1.5	1.5	1.5
18	5.5	5	4.5	4	3.5	3	3	2.5	2.5	2.5	2	2	1.5	1.5	1.5
20	5.5	5	5	4	3.5	3	3	2.5	2.5	2.5	2	2	2	1.5	1.5
24	5.5	5.5	5	4	3.5	3	3	2.5	2.5	2.5	2	2	2	1.5	1.5
30	5.5	5.5	5	4.5	3.5	3.5	3	2.5	2.5	2.5	2	2	2	1.5	1.5
36	6	5.5	5	4.5	3.5	3.5	3	3	2.5	2.5	2	2	2	1.5	1.5
48	6	5.5	5	4.5	3.5	3.5	3	3	2.5	2.5	2	2	2	1.5	1.5

*Thicknesses calculated are based on the ambient conditions stated above. This table does not imply or designate correct thicknesses for every condition, nor does it take fragility and safety into account when determining thicknesses.